



# Indoor IP Camera

Ova Pametna P2P Kamera kombinuje HD video kameru bežičnom i cloud konekcijom da donese HD video iz Vašeg doma gdje god da se nalazite, na lokalnoj mreži ili preko Interneta, preko povezanog uređaja po Vašem izboru (iOS, Android, i Windows besplatne aplikacije dostupne!). Kao dio Zipato Smart Monitoring Kit-a, možete je koristiti da vidite live i snimljene video zapise o bilo kojem alarm događaju, dobijete prikačeni video uz upozorenja ili da uvijek znate da su Vaša djeca sigurna. U kombinaciji sa povezanim uređajima, može biti dio virtualno neograničenog broja automatskih scenarija koje kreirate koristeći Zipato Rule Creator.

## KARAKTERISTIKE

- Ugrađeni Wi-Fi modul, 802.11 b/g/n
- Dnevni/noćni nadzor
- Dual Stream, H.264/MJPEG video Compression
- 3.6MM lens, F2.0
- 720p rezolucija
- Two-way Audio
- Podržava ONVIF and RTSP protokol
- Utor za SD karticu – za skladištenje snimaka
- Dual Stream, H.264/MJPEG video compression
- Alarm o detekciji pokreta putem E-mail-a, FTP i Mikro SD-a
- WPS – One Button Push Secure Wireless Connection



## TEHNIČKE SPECIFIKACIJE

### OPERATING CONDITIONS:

- POWER SUPPLY DC 5V

### OPERATION SYSTEM

- Embedded operating system

### NETWORK

- TCP/IP, UDP/IP, HTTP, SMTP, FTP, DHCP, DDNS, UPNP, NTP, RTSP, ONVIF
- LAN port; 10Base-T/100Base-TX
- Wi-Fi 802.11 b/g/n

### IMAGE PERFORMANCE

- Resolution: 1280×720, 640×360, 320×180
- Compression mode: H.264/M-JPEG
- Max frame rate: 25fps
- LENS F = 3.6mm, F = 2.0

### SENSOR

- CMOS Sensor

### ENVIRONMENT PARAMETERS

- Temperature: -10°C to 50°C (14°F to 122°F)
- Humidity: below 85% RH

**ALARM IN/OUT** In support of the 1 road

**DIMENSIONS** IP Camera:

- Device measures 60 x 40 x 95 mm
- Package: 141 x 90 x 177 mm
- Device weight: 87g
- Package weight: 337g

### REGULATION

- EMC 2004/108/EC,
- R&TTE 1995/5/EC,
- LVD 2006/95/EC,
- FCC Part 15

### ADDITIONAL FEATURES

- Video control support
- Two-way voice talkback
- Motion detection
- External alarm
- Platform level angle 350 °, 100 °vertical angle
- Audio input with microphone
- Audio output
- Support for MS Windows 98/2000/XP/Vista/Windows 7/Mac OS
- Electronic shutter
- SNR Safety performance Install mode

**WARRANTY** 1 year standard