



# Indoor PTZ IP Camera

Zipato PTZ IP Kamera kombinuje HD video kameru sa bežičnom i cloud konekcijom da donese detaljan HD video iz Vašeg doma gdje god da se nalazite, na lokalnoj mreži ili preko Interneta, preko povezanog uređaja po Vašem izboru (iOS, Android, i Windows besplatne aplikacije dostupne!). Pan-tilt-zoom mehanizam sa daljinskom kontrolom pokreta i uvećanja će se pobrinuti da svaki ugao sobe bude pokriven. Kao dio Zipato Smart Monitoring Kit-a, možete je koristiti da vidite live i snimljene video zapise o bilo kojem alarm događaju, dobijete prikačeni video uz upozorenja ili da uvijek znate da su Vaša djeca sigurna. U kombinaciji sa povezanim uređajima, može biti dio virtualno neograničenog broja automastkih scenarija koje kreirate koristeći Zipato Rule Creator.

## KARAKTERISTIKE

- Ugrađeni Wi-Fi modul, 802.11 b/g/n
- Dnevni/noćni nadzor
- Dual Stream, H.264/MJPEG video Compression
- 3.6MM lens, F2.0
- 720p rezolucija
- Two-way Audio
- Podržava ONVIF and RTSP protokol
- Utor za SD karticu – za skladištenje snimaka
- Dual Stream, H.264/MJPEG video compression
- Alarm o detekciji pokreta putem E-mail-a, FTP i Mikro SD-a
- WPS – One Button Push Secure Wireless Connection



## TEHNIČKE SPECIFIKACIJE

### OPERATING CONDITIONS:

- POWER SUPPLY DC 5V

### INTERFACE

- One 10/100Mbps RJ45
- WI-FI Support
- Power Interface
- Reset Button
- Built-in MicroSD socket
- Built-in Microphone and speaker
- 3.5mm Audio In/Out Interface
- 12 infrared LED, 8m distance

### PAN/TILT

- Horizontal: 350°
- Vertical: 90°

### IMAGE PERFORMANCE

- Image sensor: 1/4" CMOS Sensor
- Display resolution: 1280×720, 640×360, 320×180
- Lens: 1.0 Mega Pixel lens, f=3.6mm, F=2.0
- View angle: 60 degree
- IR-cut filter

### WIRELESS

- Wireless speed: IEEE802.11b/g/n 150Mbps
- Operating frequency: 2.4 GHz
- Channel: 1~13
- Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
- WPS: One key configure wifi

### SOFTWARE FEATURES

- Account permissions: Three level
- UPNP, HTTP, UDP/IP, DDNS, P2P
- Image compression: H.264/MJPEG
- Maximal frame rate: 30fps
- Code rate: 256kbps ~ 4096kbps
- Motion detection: Support four motion detection areas, send alarm pictures or video to email/FTP/MicroSD
- Image settings: saturation, brightness, contrast adjustable through client software or web browser

### AUDIO

- Two-way audio
- Audio Compression standard: AAC

### ENVIRONMENT PARAMATERS

- Operating temperature: -10°C to 50°C
- Storage temperature: -40°C to 70°C
- Operating humidity: 10% to 90%
- Storage humidity: 3% to 90%

### DIMENSIONS

- IP Camera: 106 x 117 x 126 mm
- Package: 220 x 150 x 130 mm

### WEIGHT

- Camera: 87g
- Package: 337g

### REGULATION

- EMC 2004/108/EC, R&TTE 1995/5/EC, LVD 2006/95/EC, FCC Part 15

**WARRANTY** 1 year standard